

EnBon

R5 Model

It Can Be Maintained Front And Back



ENBON GROUP
Spirit & Success, Together



+86-755-2357 0137



enbon led display



enbon led display



www.enbon.com



enbondisplay




enbon led display




Fast Lock And Arc Lock

Fast Lock



0°

Arc Lock



±7.5°
±5°
±2.5°
0°





Lighter **W**eight Easier **O**peration

20% lighter than normal products
Making it more convenient to operate and move




L*H: 250*250(mm)

Module




L*H: 500*500(mm)

Cabinet



L*H: 500*1000(mm)



ENBON GROUP
Spirit & Success, Together



+86-755-2357 0137



www.enbon.com



enbon led display



enbondisplay



enbon led display



enbon led display



Thinner Panels Lower Cost

6 in 1 flight case saves more space
and transportation cost



24 panels can be placed horizontally
in a regular 20-foot or 40-foot truck

85mm
Panel Thickness



ENBON GROUP
Spirit & Success, Together



+86-755-2357 0137



enbon led display



enbon led display



www.enbon.com



enbondisplay




enbon led display




Multiple **A**ngles, **M**ore **P**ossibility


Provide a variety of splicing options to make your creativity unrestricted



R5 Model
Curved Version



Can be adjusted $0^\circ/\pm 2.5^\circ/\pm 5^\circ/\pm 7.5^\circ$ per unit



R5 Model Curved

ENBON GROUP
Spirit & Success, **Together**



+86-755-2357 0137



enbon led display



enbon led display



www.enbon.com




enbondisplay



enbon led display

EnBon


High Refresh Rate High Grayscale



Low Refresh Rate



High Refresh Rate



Low Grayscale



High Grayscale

ENBON GROUP
Spirit & Success, Together



+86-755-2357 0137



enbon led display



enbon led display



www.enbon.com




enbondisplay



enbon led display



Product Details




Can Do Seamless Splicing




Curve Lock



Corner Cover



Power Box



Fast Lock
Between Left and
Right Cabinets



Stowing **A**nd **H**anging

Optional vertical installation and hanging beam installation



Hanging Beam Installation



Vertical Installation





Product Specification

Advanced locking system safety, Mechanism enables one-man installation

	Indoor					Outdoor		
Pixel Pitch	1.56	1.95	2.604	2.976	3.91	2.604	2.976	3.91
LED Lamp	SMD1212	SMD1515	SMD1515	SMD2020	SMD2020	SMD1415	SMD1415	SMD1921
Density (dots/m2)	410881	262144	147456	112896	65536	147456	112896	65536
Brightness	≤800 nits	≤800 nits	≤800 nits	≤800 nits	≤800 nits	≥4000 nits	≥4000 nits	≥4000 nits
IP Rating	IP45	IP45	IP45	IP45	IP45	IP65	IP65	IP65
Cabinet Materiel	Die-casting Aluminum					Die-casting Aluminum		
Refresh Rate(Hz)	3840 - 7680					3840 - 7680		
Scan	40 scan	32 scan	32 scan	21 scan	16 scan	32 scan	21 scan	16 scan
Module Weight	0.5 kg	0.5 kg	0.5 kg	0.5 kg	0.5 kg	0.5 kg	0.5 kg	0.5 kg
Cabinet Weight	7.5kg	7.5kg	7.5kg	7.5kg	7.5kg	8 kg	8 kg	8 kg
Module Size (mm)	250*250	250*250	250*250	250*250	250*250	250*250	250*250	250*250
Cabinet Size (mm)	500*500*85	500*500*85	500*500*85	500*500*85	500*500*85	500*500*85	500*500*85	500*500*85
Module Pixel	160*160 dots	128*128 dots	96*96 dots	84*84 dots	64*64 dots	96*96 dots	84*84 dots	64*64 dots
Cabinet Pixel	320*320 dots	256*256 dots	192*192 dots	168*168dots	128*128dots	192*192dots	168*168dots	128*128dots
Max Power	600 w/sqm	600 w/sqm	600 w/sqm	600 w/sqm	600 w/sqm	750 w/sqm	750 w/sqm	750 w/sqm
Average Power	360 w/sqm	360 w/sqm	360 w/sqm	360 w/sqm	360 w/sqm	450 w/sqm	450 w/sqm	450 w/sqm
Viewing Angle	H140 (+70/-70) deg V140 (+70/-70) deg					H140 (+70/-70) deg V140 (+70/-70) deg		
Control Way	Synchronous / Asynchronous					Synchronous / Asynchronous		
Gray Scale	16 bit					16 bit		
Operating System	AV, S-Video, VGA, DVI, YPbPr, HDMI, SDI					AV, S-Video, VGA, DVI, YPbPr, HDMI, SDI		
Work Humidity e	10% ~ 90%					10% ~ 90%		
Work Temperatur	-20 ~ + 65°C					-20 ~ + 65°C		

Shenzhen Enbon Optoelectronic CO.,LTD

3/ F, Building 1, High-tech Park,Fuyuan Road No.156, Fuhai Street,
Fuyong Town,Baoan District, Shenzhen, China



+86-755-2357 0137



www.enbon.com



enbon led display



enbondisplay



enbon led display



enbon led display