

EnBon

FR Model

Outdoor Fixed Front And Back Service Design



ENBON GROUP
Spirit & Success, **Together**



Enbon



Enbon **Led** Display



Different **M**odules Use **S**ame **HUB**

Customize The Box Size
According To The Display Size



L*H: 320*160(mm)

Module



L*H: 960*960(mm)

Cabinet



Weight 28kg

ENBON GROUP
Spirit & Success, **T**ogether



Enbon



Enbon **L**ed Display



Thinner Panels Lower Cost

10 in 1 flight case saves more space
and transportation cost



96 panels can be placed horizontally
in a regular 20-foot or 40-foot truck

120mm
Panel Thickness



ENBON GROUP
Spirit & Success, **Together**




Enbon



Enbon **Led** Display

EnBon

High Refresh Rate
High Grayscale



Low Refresh Rate



High Refresh Rate



Low Grayscale



High Grayscale

ENBON GROUP
Spirit & Success, **Together**



Enbon



Enbon **Led** Display




Stowing **A**nd **H**anging

Optional vertical installation and hanging beam installation



Hanging Beam Installation



Vertical Installation



Product Specification

Advanced locking system safety, Mechanism enables one-man installation

Pixel Pitch	2.5	3	3.33	4	5	6
LED Lamp	SMD1415	SMD1415	SMD1921	SMD1921	SMD1921	SMD2727
Density (dots/m2)	160000	105625	90000	62500	40000	27889
Brightness	≥5500 nits	≥5500 nits	≥5500 nits	≥5500 nits	≥5500 nits	≥5500 nits
IP Rating	IP65	IP65	IP65	IP65	IP65	IP65
Cabinet Materiel	Die-casting Aluminum					
Scan	16 scan	13 scan	12 scan	10 scan	8 scan	6 scan
Module Weight	0.5 kg	0.5 kg	0.5 kg	0.5 kg	0.5 kg	0.5 kg
Cabinet Weight	28 kg	28 kg	28 kg	28 kg	28 kg	28 kg
Module Size (mm)	320*160	320*160	320*160	320*160	320*160	320*160
Cabinet Size (mm)	960*960*120	960*960*120	960*960*120	960*960*120	960*960*120	960*960*120
Module Pixel	128*64 dots	104*52 dots	96*48 dots	80*40 dots	64*32 dots	48*24 dots
Cabinet Pixel	384*384 dots	320*320 dots	288*288 dots	240*240 dots	192*192 dots	160*160 dots
Max Power	750 w/sqm	750 w/sqm	750 w/sqm	750 w/sqm	750 w/sqm	750 w/sqm
Average Power	450 w/sqm	450 w/sqm	450 w/sqm	450 w/sqm	450 w/sqm	450 w/sqm
Viewing Angle	H140 (+70/-70) deg V140 (+70/-70) deg					
Control Way	Synchronous/ Asynchronous					
Gray Scale	16 bit					
Operating System	AV, S-Video, VGA, DVI, YPbPr, HDMI, SDI					
Work Humidity	10%~90%					
Work Temperature	-20 ~ + 65℃					

Shenzhen Enbon Optoelectronic CO.,LTD

3/ F, Building 1, High-tech Park,Fuyuan Road No.156, Fuhai Street,
Fuyong Town,Baoan District, Shenzhen, China



Enbon



Enbon Led Display